

## DS-K1A802 Series Fingerprint Time Attendance Terminal



### Available Models

- DS-K1A802F (Fingerprint)
- DS-K1A802EF (EM Card, Fingerprint)
- DS-K1A802MF (M1 Card, Fingerprint)

### Features

- Person information structure: based on employee ID
- Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out
- Supports multiple languages: English, Vietnamese, Brazilian Portuguese, Spanish, French, Italian, Arabic, and Thai
- Accesses to public network via EHome 4.0 or 5.0 protocol, and sets EHome parameters on the client or device
- 2.8-inch LCD screen to display time, date, week, and attendance information
- Supports registering fingerprints from the terminal to software remotely
- Max. 3000 users, Max. 3000 fingerprints, and Max. 100,000 events records
- Two attendance authentication modes: authentication by person, authentication by device
- Stand-alone operation (supports adding persons, cards, and fingerprints locally)
- Exports the swiping card data and the attendance report to the USB flash drive
- Up to 32 normal shifts, 32 man-hour shifts, and 32 attendance holiday schedules
- Generates the attendance report automatically and views the attendance data easily
- The third party arming is available
- IP address conflict detection



## Specifications

Model	DS-K1A802F	DS-K1A802EF	DS-K1A802MF
Storage	Up to 100,000 records, 150,000 attendance records	Up to 3000 valid cards, 100,000 records, 150,000 attendance records	
Operation system	Linux		
iVMS-4200	Support		
Fingerprint capacity	Up to 3000 fingerprints; up to 10 fingerprints for each person		
Card reading response duration	< 1 s		
Fingerprint recognition duration	< 1 s		
Fingerprint comparing mode	1:1 and 1:N		
FAR (False Acceptance Rate)	≤ 0.001%		
FRR (False Rejection Rate)	≤ 0.01%		
Fingerprint recognizer	Optical fingerprint recognizer module		
Card reading mode	/	EM card, including cards with special shapes; Supports reading card in metal environment	M1 card, including cards with special shapes; Supports reading card in metal environment
Card reading distance	/	0 to 5 cm	0 to 5 cm
Lithium battery	Not support		
Transmission Rate	LAN: 10/100 Mbps self-adaptive		
Wi-Fi	Support		
USB interface	USB 2.0, type A		
LCD screen	2.8-inch 320 × 240 LCD-TFT display screen		
Keypad	Physical keys (no backlight)		
LED indicator	Power/status (red/green)		
Audio	1 buzzer, 1 loudspeaker		
Power supply	12 VDC/1 A		
Working temperature	-10 °C to +55 °C (14 °F to +131 °F)		
Working humidity	10% to 90% (no condensing)		
Application mode	Indoor		
Color	Black (included), gold (optional), silver (optional), white (optional)		
Dimension (L × W × H)	140 mm × 155 mm × 30 mm (5.51" × 6.01" × 1.18")		
Installation	Surface mounting, metal door mounting, desk stand		

## Appearance



Black



Gold



Silver



White

Distributed by



## HIKVISION®

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 [216]521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com