

P200 & P260

Palm Recognition Multi-Biometric T&A Terminal with Access Control Functions



P serial is a multi-biometric identification time & attendance and access control terminal, which can connect with third party electric lock, door sensor, and exit button etc.

With the latest palm/fingerprint identification algorithm and streamlined technology, it can hold 600 palm templates and up to 10,000 fingerprint templates without dividing into groups.

Communicating via Wi-Fi, TCP/IP, and USB host, it ensures a smooth connection and data transfer. Amazing verification speed and intuitive operation process make it popular. Elaborately designed and finely processed, it matches your slap-up office perfectly.

Features



Build in PoE



Build in battery, up to 4 hours



Stable operation under strong light source





600 Palms, 3,000 Fingerprints, 10000 ID Cards and 100,000 records



1 channel auxiliary input for smoke detector connection



Multiple communicate mode, Wi-Fi, TCP/IP, 3G, USB host




Advance access function including lock connection, alarm, wiegand input and output

Specifications

Product		P200	P260	
Main	Biometric	Fingerprint and Palm		
	RF Optional	125kHz EM/13.56MHz MF		
Capacity	Max User(1:N)	10,000		
	Max Fingerprint (1:N)	3,000 standard/10,000 Optional		
	Max Palm (1:N)	600		
Interface	TCP/IP	10/100 M		
	PoE Optional	802.3 at 28W		
	Wi-Fi	802.11 B/G/N		
	3G Optional	WCDMA		
	USB	USB 2.0 (Host)		
	RS232	1 port for external printer		
	RS485		1 port for FP reader	
	Relay		2 relays	
	Wiegand		1ch In & Out	
	Input		1 Input	
Hardware	LCD	2.8" Color LCD		
	Sound	24-bit		
	Operating Temp.	0 °C- 45 °C		
	Operating Humidity	20% ~ 80%		
	Power	DC 12V 1.5A	DC 12V 3A	
	Dimensions(W x H x D mm)	213*155*107.81mm	213*155*107.81mm	
	Certificates	CE, FCC, RoHS	CE, FCC, RoHS	
Function	Standard	Automatic Status Switch, Self-Service Query, DST, T9 Input 9 Digit User ID, Scheduled Bell, Photo ID Lock, sensor, Exit button		
	Optional	ID/MF, ADMS		
Compatibility		ZKTime.net 3.0, ZKTime.web 2.0, ZKTime 5.0, ZKAccess 3.5		

Configuration



Dimensions (mm)

